

Material Safety Data Sheet



This is not a controlled document. To obtain the most recent MSDS please go to www.fueltrat.com

Hazardous Substance, Dangerous Goods

1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Diesel Fuel Biocide FT-400

Synonyms:

Diesel Fuel Biocide FT-400, 10 Litres
Diesel Fuel Biocide FT-400, 200 Litres
Diesel Fuel Biocide FT-400, 1,000 Litres
Diesel Fuel Biocide FT-400, Bulk

Mancode
FT-400/10
FT-400/D
FT-400/B
FT-400/T

Recommended use: Additive for diesel & similar fuels that; clean fuel systems; helps to remove water from fuel and controlling microbial contamination.

Supplier: Fueltrat Australia Pty Ltd
ABN: 71 006 318 494
Street Address: 30-32 Temple Drive
Thomastown VIC 3074
Australia
Telephone: +613 9465-6011
Facsimile: +613 9464-0102

Emergency telephone number: +613 9465-6011 (Monday – Friday, 9am – 4pm AEST)

2. HAZARDS IDENTIFICATION

This material is hazardous according to health criteria of ASCC Australia.

Hazard Category:

Xn Harmful
C Corrosive

Risk Phrase(s):

R34: Causes burns.
R41: Risk of serious damage to eyes.
R43: May cause sensitisation by skin contact.
Repr. Cat. 3. R63: Possible risk of harm to the unborn child.

Safety Phrase(s):

S23: Do not breathe vapour.
S24/25: Avoid contact with skin and eyes.
S36/37/39: Wear suitable protective clothing, gloves and eye/face protection.
S38: In case of insufficient ventilation, wear suitable respiratory equipment.
S62: If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail.

Class: 8 Corrosive

Product name: Diesel Fuel Biocide FT-400

Substance Key: FT000501

Issued: 10 April 2014

Version: 2.0

Page: 1 of 7

Material Safety Data Sheet



This is not a controlled document. To obtain the most recent MSDS please go to www.fueltrat.com

Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

Poisons Schedule (Aust): Not applicable

3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO.	PROPORTION
Diethylene glycol monomethyl ether	111-77-3	>60%
5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-4-isothiazolin-3-one (3:1)	55965-84-9	0.6-3.0%
Ingredients determined to be non-hazardous	-	Balance
		<hr/> 100%

4. FIRST AID MEASURES

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

Inhalation: Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical advice.

Skin contact: For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

Eye contact: Immediately irrigate with copious quantities of water for 15 minutes. Eyelids to be held open. Remove clothing if contaminated and wash skin. Urgently seek medical assistance. Transport to hospital or medical centre.

Ingestion: Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Get to a doctor or hospital quickly.

Notes to physician: Treat symptomatically. Effects may be delayed. Can cause corneal burns.

5. FIRE-FIGHTING MEASURES

Specific hazards: Combustible liquid.

Fire fighting further advice: On burning may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

Product name: Diesel Fuel Biocide FT-400

Substance Key: FT000501

Issued: 10 April 2014

Version: 2.0

Page: 2 of 7

Material Safety Data Sheet



This is not a controlled document. To obtain the most recent MSDS please go to www.fueltrat.com

Hazchem Code: 2X

Suitable extinguishing media: If material is involved in a fire use water fog (or if unavailable fine water spray), foam, dry agent (carbon dioxide, dry chemical powder).

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILLS < 100 mL

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal. Alternatively, flush to oily water collection system with copious quantities of water – washing with water dilutes FT-400, allowing natural bio-organisms to deactivate the product.

LARGE SPILLS > 100 mL

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. If contamination of sewers or waterways has occurred advise local emergency services.

Option 1. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

Option 2. Deactivate with "Fueltrat Deactivator 10 or 20". Prepare "Fueltrat Deactivator 10 or 20" and apply required amount as per label instructions. Once deactivate, flush to oily water collection system with copious quantities of water.

NOTE: Treatment with Deactivator 10 or 20 will immediately de-activate FT-400. Exposing FT-400 to air and sunlight will de-activate the product within 48 hours.

Dangerous Goods – Initial Emergency Response Guide No: 36

7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact and inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in Section 10. Store away from sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Dangerous Good Class 8 Corrosive as per the criteria of the Australian Dangerous Goods Code and must be stored in accordance with the relevant regulations.

Classified as a C1 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

Material Safety Data Sheet



This is not a controlled document. To obtain the most recent MSDS please go to www.fueltrat.com

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

National occupational exposure limits:

No value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC Australia).

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (ASCC)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering measures: Natural ventilation should be adequate under normal use conditions. Keep containers closed when not in use.

Personal protection equipment: OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES.

Wear overalls, chemical goggles and impervious gloves. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using. If risk of inhalation of exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form / Colour / Odour: Clear bright yellow to pale straw liquid with faint sweet odour

Solubility:	Soluble in water
Specific Gravity (20 °C):	1.055-1.075
Relative Vapour Density (air=1):	N Av
Vapour Pressure (20 °C):	N Av
Flash Point (°C):	93*
Flammability Limits (%):	N Av
Autoignition Temperature (°C):	N Av
Melting Point/Range (°C):	N Av
Boiling Point/Range (°C):	196-202*
pH:	N App
Total VOC (g/Litre):	N Av

* Diethylene glycol monomethyl ether
(Typical values only - consult specification sheet)
N Av = Not available N App = Not applicable

10. STABILITY AND REACTIVITY

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible Materials: Oxidising agents.

Material Safety Data Sheet



This is not a controlled document. To obtain the most recent MSDS please go to www.fueltrat.com

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material is irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin will result in severe irritation. Corrosive to skin - may cause skin burns. A skin sensitiser. Repeated or prolonged skin contact may lead to allergic contact dermatitis.

Eye contact: A severe eye irritant. Corrosive to eyes: contact can cause corneal burns. Contamination of eyes can result in permanent injury.

Ingestion: Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the gastrointestinal tract.

Long Term Effects: No information available for product.

Acute toxicity / Chronic toxicity

No LD50 data available for the product.

12. ECOLOGICAL INFORMATION

Avoid contaminating waterways. No data available for the product. However, for the constituent:

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Mobility: No information available.

13. DISPOSAL CONSIDERATIONS

Refer to State/Territory Land Waste Management Authority.

Material Safety Data Sheet



This is not a controlled document. To obtain the most recent MSDS please go to www.fueltrat.com

14. TRANSPORT INFORMATION

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail.

UN No: 3265
Dangerous Goods Class: 8
Packing Group: III
Hazchem Code: 2X
Emergency Response Guide No: 36

Proper Shipping Name: CORROSIVE LIQUID, ACIDIC ORGANIC N.O.S. (5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE, 2-METHYL-4-ISOTHIAZOLIN-3-ONE)

Segregation Dangerous Goods: Not to be loaded with explosives (Class 1), dangerous when wet substances (Class 4.3), oxidising agents (Class 5.1), organic peroxides (Class 5.2), cyanides of Class 6, radioactive substances (Class 7) or food and food packaging in any quantity, however exemptions may apply. Note that concentrated strong acids are incompatible with concentrated strong alkalis.

MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 3265
Dangerous Goods Class: 8
Packing Group: III

Proper Shipping Name: CORROSIVE LIQUID, ACIDIC ORGANIC N.O.S. (5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE, 2-METHYL-4-ISOTHIAZOLIN-3-ONE)

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

UN No: 3265
Dangerous Goods Class: 8
Packing Group: III

Proper Shipping Name: CORROSIVE LIQUID, ACIDIC ORGANIC N.O.S. (5-CHLORO-2-METHYL-4-ISOTHIAZOLIN-3-ONE, 2-METHYL-4-ISOTHIAZOLIN-3-ONE)

15. REGULATORY INFORMATION

Poisons Schedule (Aust): Not applicable

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

Material Safety Data Sheet



This is not a controlled document. To obtain the most recent MSDS please go to www.fueltrat.com

16. OTHER INFORMATION

Literary reference

This Material Safety Data Sheet has been prepared by Chemical Data Services Pty Ltd on behalf of its client.

Reason(s) For Issue: 5 year review

Material Safety Data Sheets are updated frequently. Please ensure that you have a current copy.

This MSDS summarises at the date of issue our best knowledge of the health and safety hazard information of the product, and in particular how to safely handle and use the product in the workplace. Since Fueltrat Australia Pty Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this MSDS in the context of how the user intends to handle and use the product in the workplace.

If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company.

Our responsibility for product as sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available upon request.